


The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

November 2019



CS Winding Pack and Support Structures


CS module: geometry




Similar CICC concepts



NHMFL




EU-Alt TF



The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

(All dimensions at 4 K)

CS module: winding configuration




The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS module: winding configuration



Sol. A: avvolgimento con salto spira distribuito



The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.


CS module: winding configuration




Sol. A: avvolgimento con salto spira distribuito



Vista da sopra



Vista da sotto




The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS module: winding configuration



Sol. A: avvolgimento con salto spira distribuito HF winding




The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS module: winding configuration



Sol. A: avvolgimento con salto spira distribuito LF winding




The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS module: winding configuration




Sol. A: avvolgimento con salto spira distribuito



HF winding

N.B: Con salto spira distribuito lungo 360° gli strati dell'avvolgimento risultano disallineati fra loro!



LF winding


N.B: Con salto spira distribuito lungo 360° gli strati dell'avvolgimento risultano disallineati fra loro!

The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS module: winding configuration



Sol. B: avvolgimento con salto spira concentrato




The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS module: winding configuration



Sol. B: avvolgimento con salto spira concentrato




The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS module: winding configuration



Sol. B: avvolgimento con salto spira concentrato

HF Winding



The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.


CS module: winding configuration




Sol. B: avvolgimento con salto spira concentrato



HF winding



LF winding




The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS module: winding configuration




Sol. B: avvolgimento con salto spira concentrato



HF winding

N.B: Con salto spira concentrato gli strati dell'avvolgimento risultano allineati fra loro lungo qualsiasi sezione!



LF winding

N.B: Con salto spira concentrato gli strati dell'avvolgimento risultano allineati fra loro lungo qualsiasi sezione!

The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS module: manufacturing approach



Wind & Insulate → React → Impregnate manufacturing approach

- Insulation to be applied during coil winding, before the Nb₃Sn reaction heat treatment:


→ turn insulation will not rely on Kapton: but according to computations, it is not necessary for the expected voltage levels (3.5 kV peak terminal-to-terminal Voltage at plasma breakdown);

→ most appropriate choice of insulation material (S-glass ? / resin type ?)
and manufacturing process?

CS module: HF to LF joint



- Two terminations and one inter-layer joint per module.
- Inter-layer joint: **either** manufactured on the external part of the coil, **BUT** 65 mm clearance wrt TF.



DTT CS Coil_Layered_v50
Layout 1

- Joint 1: HF-LF
- Internal termination
- External termination
- He outlet
- He inlet



*2 terminations
2 intermediate joints
7 He inlets
8 He outlets*

The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.



CS module: HF to LF joint



- Two terminations and one inter-layer joint per module.
- Inter-layer joint: **either** manufactured on the external part of the coil, **BUT 65 mm clearance wrt TF**.
- **or** use “internal” joint, manufactured in-line during winding, thus embedded within the winding pack (*EDIPO / NAFASSY / ITER CS – like*).




NAFASSY Interlayer Joint





The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

NAFASSY Interlayer Joint



The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

DEMO TF Interlayer Joint




The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS module: HF to LF joint



- Two terminations and one inter-layer joint per module.
- Inter-layer joint: **either** manufactured on the external part of the coil, **BUT** 65 mm clearance wrt TF.



DTT CS Coil_Layered_v50
Layout 1

- Joint 1: HF-LF
- Internal termination
- External termination
- He outlet
- He inlet

*2 terminations
2 intermediate joints
7 He inlets
8 He outlets*

The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.


CS module: HF to LF joint



- Two terminations and ~~one~~ ^{two} inter-layer joint per module.

- STILL UNDER DISCUSSION:

LF CICC maybe too long (870m);
so, the LF Winding might be interrupted
by an additional (LF to LF) intermediate
joint.



DTT CS Coil_Layered_v50
Layout 1



Joint 1: HF-LF



Internal termination



External termination



He outlet



He inlet

*2 terminations
2 intermediate joints
7 He inlets
8 He outlets*

The material and information contained in this presentation are provided for information purposes only,
and should not construed as basis technical specifications of the call for tenders.


CS module: termination box



Still to be designed.

Space constraints are extremely demanding!

65 mm between CS and TF



The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tender.


CS module: termination box



Still to be designed.

Space constraints are extremely demanding!

What about extending terminal lengths well outside the module height, thus avoiding joints?



The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tender.

CS module: additional issues



Corner regions:

- S-glass cord


OR

- Glass insulated steel wire (useful also for co-wound V tap)

Co-wound tape for quench detection:

- fabric tape wrapped around the conductor (e.g. KSTAR CS)

CS module: additional issues




The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS module: additional issues





Additional layers useful / necessary?
(mechanically and from the
manufacturing point of view?)

1 mm
inter-grade
insulation




The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS: structures and assembly



The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS: structures and assembly



The material and information contained in this presentation are provided for information purposes only, and should not be construed as basis technical specifications of the call for tenders.

CS module preparation



Operations to complete (on each module)

1. HF grade turn insulation & winding;
2. HF He inlets welding (during winding);
3. Internal and terminal joint preparation;
4. LF grade turn insulation & winding;
5. LF He inlets welding (during winding);
6. Heat-treatment at 650°C;
7. Ground insulation application;
8. G10 inter-module grooved spacers insertion
9. VPI and curing;
10. Acceptance tests.


CS coil assembly (tbd)



Each module to be (cold) tested at ENEA. Then:

Operations to complete (6 modules)

1. Module stacking;
2. Pre-compression structures application;
3. Piping welding;
4. Acceptance tests;
5. Transport structure preparation;
6. Shipping to ENEA Frascati.




The material and information contained in this presentation are provided for information purposes only and should not be construed as basis technical specifications of the call for tenders.

Conclusions and recommendations



- Detailed engineering design still under development;
- 1 spare module and 1 assembled CS coil made of 6 stacked coils and its pre-compression structures, shall be eventually shipped to ENEA in Frascati.



The material and information contained in this presentation are provided for information purposes only and should not be construed as basis technical specifications of the call for tenders.